# Audion Hub Manager — History

Русский · About · User Guide · Decisions

**Contents**


- 2.0.0
- 1.10.0
- 1.9.0
- 1.8.0
- 1.7.3
- 1.7.2
- 1.7.1
- 1.7.0
- Earlier versions


This history exists not to count versions but to avoid fixing the same thing twice. What changed is here — and why.

## 2.0.0

**A new window on Avalonia.** The former window — a local NiceGUI web server in a pywebview frame — is replaced by a built program, `App\AudionHubManager.exe`. `Start.exe` starts it directly, with no console and no administrator rights. Seven sections across the top: CHANGES, HISTORY, BRANCHES, SYNC, MIRROR, PROJECTS, SERVICE; along the bottom, the frequent operations of a section with their fields. Four themes (VAULT, CODE, DARK, LIGHT), JetBrains Mono, a graph of commits, a file panel in the colours of Git. The projects stand in a column on the left: a click makes one the current project, the squares mark several, the root of the projects is chosen by the badge; in a narrow window the column opens over the page. A long name or message fades out at its end, with no ellipsis. The folders of projects are chosen in the folder panel of PROJECTS — each folder marked with what it is to the registry and to Git — not in the system dialog. A new icon: an orange folder with a Git branch; ABOUT shows the approved Audion logo and the links with their signs: tensionix.com, the

download page on audion.dev, the repository on GitHub, the page of the project on tensionix.github.io.

**The registry lies in the root of the projects, a commit goes to several at once.** The registry of projects is `hub_projects.json` in the root of the projects, each root with its own: change the root and the column shows its projects. A registry the program kept in `config\projects.json` moves into the root at the first start. The menu of the root imports a registry from a file and exports it into a file with full paths. COMMIT THE MARKED at the foot of the column takes every marked project through a checkpoint in its GIT COPY — the mirror, the check by BLAKE3, the secrets, the check by the profile, add and commit with one subject; a project where a step says "no" stops with the reason, the others go on.

**Every button shows its command.** All Git operations of the window are one table — the canon, 63 operations: the command, its risk, what it does and how to undo it, in two languages. A button's caption is the command as typed in a terminal. The terminal shows the command, on request what it did and how to undo it, the output of git in colour and the outcome with its exit code. A dangerous operation asks first, showing the whole command, what is not committed now and how to undo it; `reset --hard` is confirmed by typing the word RESET.

**The lab.** `hub_cli.cmd lab create` builds ten repositories to learn on: the first commit, the index, branches and a merge, a conflict, being behind a server, stash, tags, a lost commit, revert and reset, a mirror. Their authors and dates are fixed, so the hashes are the same on any machine. Every operation of the canon is checked by a test on a fresh copy of the lab; the five network ones (ssh, gh, glab), by the shape of the command.

**The console door `hub_cli.cmd`.** Everything the window does beyond Git is a command printing one JSON document: the project registry, the mirror, the profile check of paths before the index and a commit (a file outside the profile does not get into a commit), the secret scan, storage, BLAKE3, Forgejo. The former `system_core\main.py` and the four `launcher_*.cmd` are gone.

**Its own PowerShell 7 — `App\AudionPs.exe`.** The portable PowerShell in `system_core\powershell` (a quarter of a gigabyte) is gone; building the environment, checking the CMD files and cleaning the cache run on the program's own. Python is unpacked by .NET: the program's PowerShell has no archive module.

**The environment is half the size.** The packages of the former window (nicegui, pywebview, rich, tqdm, beautifulsoup4) are gone, `runtime\` is 60 MB instead of 129. httpx is named explicitly now: the Forgejo client imports it, and it used to arrive only along with nicegui.

**Cleaning the project no longer destroys the program.** `cleanup_project.cmd` deleted every `*.exe` and `*.dll` in the tree — the built window and `Start.exe` with them. It now passes them by, and removes the state of the window and what building it leaves (`Source\bin`, `Source\obj`).

`doctor.py` **tells the truth.** It checks the packages of the engine, BLAKE3, the canon, git and the files of a release, and fails when something is missing; it used to always succeed. `install\verify_portable_env.cmd` also checks the door and the built window — by the window's own report.

**A GIT COPY for a project of any kind.** The profile knows the sources, builds and CI of the common languages — Python, .NET, the web, Go, Rust, Java, Swift, Flutter, Unity, Godot and more — and keeps out dependencies, builds, caches, secrets, media, archives, models and databases; pictures and fonts of the sources pass up to a megabyte. Hundreds of masks are checked in a fraction of a second; the profiles shipped put no `.gitkeep` markers, and what the project's `.gitignore` hides is never offered to a commit. The registry keeps the paths of folders inside the root of the projects relative — the root moves together with its registry; a new repository starts with the project's branch (`git init -b main`).

**The mirror never writes through a link.** The walks of the SOURCE and the GIT COPY followed junctions: a junction inside the GIT COPY could carry a write into the SOURCE, and a file the walk could not read dropped out of the plan silently — and its copy was deleted. Now neither walk follows a symbolic link or a junction, every write checks where its path really leads, and an unread file is an error of the plan that stops the deletions. The secret scan counts a file it could not read (held by another program) as an error, not as a clean file; the batches count the errors inside each project; a typed command is judged by its arguments, `push -f` or `clean -fdx` inside a line of PS as well.

**The documents describe the program as it is, in two languages.** The Git wiki gathers every command by the sections of the window: what each does and how to undo it, the four places of Git, Git words in plain words, common situations and what to do, the Git lab. A new reference of the console command (`CLI_EN.md`). `hub_cli.cmd canon --docs` writes the tables of commands from the canon, and a test keeps them from falling behind the buttons.

Removed: builder steps 04 (portable PowerShell), 74–78 (licences and the archive — Audion Build Licenses and Audion Build Publisher do those), 90, 91 and 99; `system_core\license`, the template cleaner, the empty `data`, `backup`, `release`; engine code only the former window called: the HTML terminal, the Git actions of its buttons, opening VS Code and the browser, the parser of commands of its command line.

## 1.10.0

**A corrupt registry no longer blocks startup.** A single stray comma in `config/projects.json` used to abort the program with a traceback before the window opened: the registry was read with a raising JSON loader on import. Startup config reads now fall back to defaults, keep the surviving records, and report the problem in the output dock. An empty or unreadable registry yields a temporary project pointing at the program itself — the window opens, and the config can be fixed from inside it.

**Mirror plans are re-validated at apply time.** Applying trusted the roots stored in the plan file, so a stale or edited plan could delete under a path overlapping the source. The profile and the non-overlapping-roots rule are now re-checked before anything is written or removed.

**Behaviour change: a copy error blocks deletion unconditionally.** Previously `delete_after_successful_copy: false` let deletion proceed after failures — exactly the case where a mirror can drop files that exist nowhere else. The setting remains in the config but can no longer disable that protection.

**Commands run through the engine, not through a shell string.** Bundle creation and fast-forward pull composed a command line in the GUI, interpolating a filesystem path into it: a folder name containing `&` or a quote would have broken it. Both now run as argument lists. The engine functions existed all along and were simply never called.

**Taskbar identity.** A name that already begins with the brand no longer gets a second prefix: the app is `Audion.Hub.Manager` rather than `Audion.Tools.Audion.Hub.Manager`. Windows groups taskbar windows by this id.

**A new icon** — a white three-armed hub mark on a near-black rounded tile, rendered at 16 through 256 pixels, with a simplified variant below 32 where the three nodes collapse into a blur. The previous icon is kept.

Two server helpers that nothing used were removed.

## 1.9.0

**The token works immediately.** Every button used to read the token back from the credential store, so one typed into the field did nothing until it was stored — saving was a precondition for anything working, rather than a convenience. The typed token is now used at once, and "remember token" does what its name promises: keeps it across restarts. The status line names which token the buttons are about to use.

**Forgetting clears both places at once** — the field and the remembered copy in the credential store.

## 1.8.0

**Cloning arrived in the Remote pane,** which had no cloning action at all. It takes the address from the field, clones next to the active project folder, refuses to clone onto an existing folder, and runs `git` as an argument list rather than through a shell.

**Cloning no longer hangs.** It runs with terminal prompts disabled: a credential prompt has no way to reach you from the window, so instead of waiting into the void the program warns that Git reads the store, not the form.

**The Remote pane remembers your choice** — platform and address type across sessions — and opens where you left it instead of resetting to GitHub.

## 1.7.3

**Token scopes follow the route, not the object.** Per-operation testing against a live Forgejo 15 showed that creating a repository sits under `/api/v1/user/*` and therefore needs a user scope, not a repository one. Git over HTTPS is judged separately and needs a repository scope regardless — one set of scopes cannot cover both the API and git.

**Documented what is wrong with a credential-bearing address:** Git writes that token in the clear into `.git/config` of the working copy, where it survives every backup and mirror of that folder. The same family of mistake as a secret in a URL query parameter, and avoided entirely by the credential-helper path.

## 1.7.2

**A command-injection path was closed.** URL parsing keeps `;`, `&&`, and `$(…)` inside a hostname, and that hostname was interpolated into an `ssh -T` probe the GUI runs through a shell. A `forgejo_hosts.json` arriving with a cloned project could therefore run a command on the first probe. Hostname, SSH user, and port are now validated where every path converges, hostile records are dropped instead of loaded, and addresses embedding credentials are refused outright.

**Addresses that make Git execute a command are refused** (`ext::`, `fd::`), along with addresses starting with a dash — Git would read them as an option — and addresses carrying control characters. Validation runs both when saving from the pane and when applying a config file, so one from another project cannot smuggle such an address in.

**A warning when a host is reached over plain HTTP** before a token is sent: legitimate for a LAN instance, but the token crosses the wire unencrypted.

## 1.7.1

**A server typed into the form is no longer dropped.** The config write went through a function that returns early when the login already matches, so the host was never written to file and had to be retyped on the next start.

**Config parsing became fault-tolerant.** A hand-edited file with a syntax error used to raise straight into an event handler, because the pane reads it on every platform switch and every keystroke in the server field.

**The repository list is no longer silently truncated.** Paging stops at a thousand entries, and reaching that ceiling is now reported rather than presented as a complete list.

**An unusable SSH port is rejected** instead of quietly substituting 22, which built a plausible-looking address that failed later at push time.

**An address with an embedded login or token is not saved** into `config/remotes.json` — a committed file, where the secret would have been published with the next commit.

**Erasing a token requires a named account:** credential helpers key entries by host *and* username, so an empty login matched nothing while reporting success.

## 1.7.0

**Support for self-hosted Forgejo and Gitea.** `config/forgejo_hosts.json` describes servers — address, SSH user and port, preferred address type, cached login — and holds no secrets.

**The ordinary account contract was adopted:** a personal access token, verified against the server and handed to the credential helper. Nothing is written into project config, and plain HTTPS push picks the same credential up.

OAuth2 sign-in was evaluated and rejected for now: Forgejo has not implemented OAuth2 scopes, so such tokens carry administrative account rights, expire quickly, and cannot serve push unaided.

**403 is separated from 401 in every call.** An insufficient scope now reports "the token is valid but was created without the scope this call needs", names the scope the server asks for, and suggests the working set — instead of a bare status code alongside a token that is in fact correct.

**Server error text is redacted before display.** Forgejo quotes an unknown token back in its message, so a revoked or expired token would have appeared verbatim in the output dock, and from there in screenshots and copied output.

**The 413 case is documented** for instances behind a proxy or tunnel with a request-body cap: it is the initial history push that hits it, and pushing over SSH — including through a local port forward — is the way around it.

## Earlier versions

`0.2.x` — planning: mirror safety contracts, layer separation, filtering profiles. `v0.1.0` — the application skeleton.

What carried over from that period are the rules set out in Decisions: collected from real Disk Auditor failures, and not worth learning twice.